\setminus		DEVIATIO		OLERANCED DI	$\overline{}$			_	CE FINISH		,	=
	THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF DMIPL AND IT SHALL NOT BE USED,	DIMENSION	OVER	0.5 3	6 30 120	400 1000 20	- HOOGINE				ROUGH MACHINI	.NG
	REPRODUCED OR DISCLOSED TO OTHERS IN WHOLE OR IN PART WITHOUT THE EXPRESS PERMISSION OF DMIPL		UP TO & IN	-	-	1000 2000 40		$\neg \vdash \nabla$		- ⊸	RM	_
lt	ANY MANUAL ALTERATION WITHOUT AUTHORISED SIGNATURE	MACHINE TOI FABRICATION		-	±0.2 ±0.3 ±0.5 ±0.5 ±0.8 ±1.2	±0.8 ±1.2 ± ±2 ±3 ±	HOUGHINE		0.8	3.2 6.3	25	
╏╏	SHALL AUTOMATICALLY RENDER THIS DRAWING INVALID	TABILICATION	ISSUE		20.0 20.0 21.2		RIPTION	•			ATE S	1
			R1					- d			.07.21 SS	
			n i	Diowe	Caulloi	n Detail	s are Adde	e a		30,	07.2133	>r\
												_
Н					-		296±1		-			
						1224	n 2	122±0.2				
				_		133±	0.3	133±0.3	1			
				1	_ 		•		.∳}			
2	All Dimono	ons are in m	am		82.5±0.3		42±1	Ť				2
	All Diffiers	ons are in ii		+1	32.5		42±1	-				
				194±1	∐ ⊢⊙			40 ± 1	0			
					9			4		0 x 8 Hole	<u>S</u>	
Н					82.5±0.3			Ų.	AS	Shown		\vdash
				,	~1)	0	,	6)			
				,								
	397	+2			 =		291±2		-			
3	337	- 				_	245±2	_	_			3
		_1						-]			
									1			
	otation					1						
Н	27 15 Significant Production	\equiv			¶	ŀ			P			\vdash
	351+2	\pm	• ~	\	Air Inlet				Air	Inlet		
			\bigcirc	7					∭⋖			
			.)	Щ	Щ				1 1			
4	\ \ \ \ \ \ \ \ \ \ \ \ \ \		1		9							4
		∕ € \}}}	IIII	П				_		-		
	42 7		////	4	Ħ	_	/					
	17 17 17 17 17 17 17 17 17 17 17 17 17 1	=	$\bigcup /$		\	l er	minal Box (=	-				
Ш	15.		•/									L
					d				Ь			
					_	1			<u>E</u>			
Ш												
5	Performance Data											5
	1 onormando Bata		Т,	Max power								
			" U"	Input	Current	Speed	Capacitor	Max Inlet	weight	Noise		
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		ssure nwc	Watt	A ±10%	RPM ±5%	Value mfd	Air Temp °C	Kg	level dbA		
				±10%				_				L
	DB24S4 240V,1Ø,50 HZ 2	700 4	10	760	3.3	1300	16	60	14.5	72		
П	Maximum Vibration Limit: Velocity-2.8	mm/sec RMS	(8 mm/se	ec-Pk-Pk)		•						
	as per ISO 14694-2003-GradeB V3 Ta		,	•	f Routine	Tests Co	nducted:					
6	Air Output Vs Static Pr	1					Motor				6	
П	40	2	Measurement Of Winding Resistance of Motor Measurement of parameters like Current, Power and Speed at Rated									
П	ŷ			Supply With			iet.					
	32			3. High Volta For 240V: 1								
Ιl	_						0\/ D0 M	aer Minim	um			L
ш					Resistanc							
Н	9 24 24						5 Meg Ohm					- 1
	9 24 S		lr <u>1</u>	nsulation Re <u>Note:</u>	esistance	Shall be	5 Meg Ohm.		amb:			l l
	d 16		Ir <u>1</u>	nsulation Re <u>Note:</u> Air Output Ar	esistance nd Pressur	Shall be	5 Meg Ohm.	reference				
7	atic Pressure -		lr <u>1</u> 2 0	nsulation Re <u>Note:</u> Air Output Ar Due to contin change with	esistance nd Pressur nuous deve out prior no	Shall be to determine the dete	5 Meg Ohm. e provided for the above da	reference ta are subje				7
7	9 24 24 24 24 24 25 24 25 24 25 25 25 25 25 25 25 25 25 25 25 25 25		Ir <u> </u>	nsulation Re <u>Note:</u> Air Output Ar Due to contin change with Air output - C	esistance and Pressur nuous deve out prior no Conversion	Shall be a celopment, otice.	5 Meg Ohm. e provided for the above da ultiply "m³ /hı	reference ta are subje	ct to			7
7	Static Pressure		r 	Note: Air Output Ar Due to contin change with Air output - C Static Pressu	nd Pressur nuous deve out prior no Conversion ure - Conve	Shall be a celopment, otice.	5 Meg Ohm. e provided for the above da	reference ta are subje	ct to			7
7	Static Pressure		r 	nsulation Re <u>Note:</u> Air Output Ar Due to contin change with Air output - C	nd Pressur nuous deve out prior no Conversion ure - Conve	Shall be a celopment, otice.	5 Meg Ohm. e provided for the above da ultiply "m³ /hı	reference ta are subje	ct to			7
7	Static Pressure	2500 300	Ir <u> </u>	nsulation Re Note: Air Output Ar Due to contin change with - Air output - C Static Pressu CAUTION: BLOWER NOT	nd Pressur nuous deve out prior no Conversion ure - Conve	Shall be a red data are elopment, otice. to cfm: mersion to p	provided for the above da ultiply "m ³ /hr ascal: multip	reference ta are subjet by 0.59 by "mmwc" l	ct to by 9.81	· ONI V		7
7	24 16 500 1000 1500 2000	2500 300	Ir 	nsulation Re Note: Air Output Ar Due to contin change with - Air output - C Static Pressu CAUTION: BLOWER NOT	nd Pressur nuous deve out prior no Conversion ure - Conve	Shall be a red data are elopment, otice. to cfm: mersion to p	5 Meg Ohm. provided for the above da ultiply "m³ /hı ascal : multipl EE INLET AND I UULD BE OPER	reference of tall are subject of the	ct to by 9.81 T. 10MMWC			
7	500 1000 1500 2000 Air Output-m ³ /Hr			nsulation Re Note: Air Output Ar Due to contin change with Air output - C Static Pressu CAUTION: BLOWER NOT MOTOR MAY C	nd Pressur nuous deve out prior no conversion ure - Conve BE OPERAT GET TRIPPE	Shall be a data are elopment, otice. to cfm: mersion to p	provided for the above da ultiply "m³ /hı ascal : multip EE INLET AND I SULD BE OPER	reference of tall are subject of the	ct to Dy 9.81 T. 10MMWC	01,DB24-1		09
7	24 16 500 1000 1500 2000		Ir 1 C C C C C C C C C C	Note: Air Output Ar Due to contin change with Air output - C Static Pressu CAUTION: BLOWER NOT MOTOR MAY C	nd Pressur nuous deve out prior no Conversion ure - Conve 1) BE OPERAT GET TRIPPE	Shall be a data are elopment, otice. to cfm: mersion to p	5 Meg Ohm. provided for the above da ultiply "m³/hi ascal : multiple EE INLET AND I ULLD BE OPER Superse	reference of tall are subject of the	ct to Dy 9.81 T. 10MMWC :DB24-1	01,DB24-1 AS PER IS:210		
7	24		Irr	nsulation Re Note: Air Output Ar Due to contin change with Air output - C Static Pressu CAUTION: BLOWER NOT MOTOR MAY C	nd Pressur nuous deve out prior no conversion ure - Conve BE OPERAT GET TRIPPE	Shall be re data are elopment, otice. to cfm: mersion to predict of the property of the proper	5 Meg Ohm. provided for the above da ultiply "m³/hi ascal : multiple E INLET AND I ULLD BE OPER Superse NON UNTOLERAN E : Specification DB24	reference of tall are subject of the	Ct to Dy 9.81 T. 10MMWC DB24-1 NARE TO BE SC/	01,DB24-1 AS PER IS:210 ALE - NTS FIF	1-MEDIUM CLAS	09 88 30J
	24		Irr	Note: Air Output Ar Due to contin change with Air output - C Static Press CAUTION: BLOWER NOT MOTOR MAY C	nd Pressur nuous deve out prior no conversion ure - Conve 1) BE OPERAT GET TRIPPE	Shall be re data are elopment, otice. to cfm: mersion to predict of the property of the proper	5 Meg Ohm. e provided for the above da ultiply "m³ /hi ascal : multip EE INLET AND I ULD BE OPER Superse N ON UNTOLERAN E : Specification DB24*	reference of the task of the t	Ct to Dy 9.81 T. 10MMWC :DB24-1 NARE TO BE SC/ ISS	01,DB24-1 AS PER IS:210	1-MEDIUM CLAS	
	24 500 1000 1500 2000 Air Output-m / Hr SURFACE PROTECTIO TYPE OF PROCESS SPECIFICATION COATING AREA FINISH		Irr	nsulation Re Note: Air Output Ar Due to contin change with Air output - C Static Pressu CAUTION: BLOWER NOT MOTOR MAY C MIN () IS FOR RE LLL DIMENSIONS ESIGNED BY	nd Pressur nuous deve out prior no conversion ure - Conve BE OPERAT GET TRIPPE FERENCE ONL SARE IN MM CHECKE S.S.	Shall be re data are elopment, otice. to cfm: m ersion to predict the property of the property	provided for the above da ultiply "m³ /hr. ascal : multiple EINLET AND IDULD BE OPER Superse NON UNTOLERANE: Specification DB241 PROVED BY D. S.S.K.	reference of the state are subject of the state are subject of the state of the sta	Dy 9.81 T. 10MMWC DB24-1 NARE TO BE SC/USS 10.	01,DB24-1 E AS PER IS:210 ALE - NTS FIF	1-MEDIUM CLAS	09 88 30J
	24 500 1000 1500 2000 Air Output-m /Hr SURFACE PROTECTIO TYPE OF PROCESS SPECIFICATION COATING AREA FINISH PATTERN		Irr	ASSIDENCE OF THE PROPERTY OF T	nd Pressur nuous deve out prior no conversion ure - Conve BE OPERAT GET TRIPPE GARE IN MM CHECKE S.S.	Shall be re data are elopment, otice. to cfm: mersion to present the property of the property	provided for the above da ultiply "m³ /hi ascal : multiple EE INLET AND INULD BE OPER Superse NON UNITOLERAN E: Specification DB24: PROVED BY D.S.S.K	reference of tall are subjection of the subjecti	Dy 9.81 T. 10MMWC DB24-1 NARE TO BE SC, 10. CIFICATIO	01,DB24-1 AS PER IS:210 ALE - NTS FIF UED DATE	1-MEDIUM CLAS RST ANGLE PF	09 ss ROJ 8
	24 500 1000 1500 2000 Air Output-m / Hr SURFACE PROTECTIO TYPE OF PROCESS SPECIFICATION COATING AREA FINISH	N DETAILS	Irr	ASSIDENCE OF THE PROPERTY OF T	nd Pressur nuous deve out prior no conversion ure - Conve BE OPERAT GET TRIPPE FERENCE ONL S ARE IN MM CHECKE S.S.	Shall be re data are elopment, otice. to cfm: mersion to present the property of the property	provided for the above da ultiply "m³ /hi ascal : multiple EE INLET AND INULD BE OPER Superse NON UNITOLERAN E: Specification DB24: PROVED BY D.S.S.K	reference of the state are subject of the state are subject of the state of the sta	Dy 9.81 T. 10MMWC DB24-1 NARE TO BE SC, 10. CIFICATIO	O1,DB24-1: AS PER IS:210 ALE - NTS FIF UED DATE 02.2021 DN DB24S4	1-MEDIUM CLAS RST ANGLE PF	09 ss ROJ 8